



HALO2000 AC1200 2KWh Solar Generator

AC1200W/PV1000W/Battery2000+Wh



PRODUCT FEATURES



Multi-Protection:

Overload, overvoltage and short circuit protection




Simple Design:

Plug and play




Quick Charge:

PV+AC fast charging, efficient energy storage



Three-In-One System:

MPPT + Inverter + Battery integrated



High Performance:

Pure sine wave, UPS class switch time: <20ms



LCD Display:

Real-time status monitoring

TECHNICAL SPECIFICATIONS



PV INPUT

Max. Input Power	1000W
Max. Input Voltage	60Vdc
MPPT Voltage Range	12-55Vdc
Max. Input Current per MPPT	25A
Max. Charging Current	100A
Number of PV Input Ports	2
MPPT Efficiency	99%

AC INPUT

Rated Input Voltage	230Vac
Rated Input Frequency	50/60Hz
Input Frequency Range	45-65Hz
Input Voltage Range	90-280Vac
Max. Input Power (Charging+Load)	1800W

AC OUTPUT

Rated Output Power	1200W
Rated Output Voltage	230Vac
Nominal Output Frequency	50/60Hz
Waveform	Pure Sine Wave
Output Voltage Type	L/N/PE
UPS Switch Time	≤20ms
Overload Capacity	CP1200W Latch output@<200Vac

BATTERY PACK

Cell Type	LFP
Rated Voltage	6.4Vdc
Capacity	314Ah
Energy	2009.6Wh
Cycle Life	6000

GENERAL DATA

Operating Temperature	0~50°C (>40°C Power Derating)
Operating Humidity	20%~95% (Non-condensing)
Max. Operating Altitude	3000m (>2000m Power Derating)
Dimensions	420*148*290mm
Weight	19.8KG
Ingress Protection	IP31
Noise	<50dB

PROTECTION

Overload Protection	√
Short Circuit Protection	√
Over Temperature Protection	√
Battery Overvoltage Protection	√
Battery Undervoltage Protection	√
PV Reverse Polarity Protection	√

